

## GAP10 GAS ALARM CONTROL PANEL

- 8 pieces gas alarm detector (4-10 Ma output) can be connected.
- 2 pieces tank level switch can be connected.
- There are 8 different timers for gas alarm detectors.
- For each tank level sensor, there are 2 different high and low level timers.
- There are 2 different language option: English and Turkish
- Gas alarm detector and tank level sensor can be changed active and passive condition separately.
- 128x64 graphic LCD display. (Tank occupancy rate can be displayed visually.)
- Signal error can be displayed by the screen.

**Size** : (G x D x Y) 144 x 135 x 144 mm  
**Weight** : 0.60 kg  
**User Interface** : 128\*64 Blue-White Grafic LCD -display  
Rotating Set Switch  
Button Switches



### Environmental Working Conditions

**Working Temperature Range** : -10 °C - 40 °C  
**Humidity** : %30 - %75  
**Voltage** : 230V AC  
**Frequency** : 50Hz/60Hz  
**Suggested Protection Fuse-box** : 2A B type Automat Fuse-box  
**Output Power** : 4 W  
**Signal Input and Type** : 8 pieces 4-20mA,  
2 pieces 1-5VDC  
**Dedector Supply Voltage** : 12V DC  
**Tank Level Supply Voltage** : 5 VDC  
**Compatible Detectors** : 4-20mA output current,  
All detectors which gives 1-5  
VDC output tension  
**Control Output and Control Type** : 8 pieces, Max. 5A/250