

Accessories

Electrodes:



	LF 200 RW	LF 210
Measuring range:	0 ... 100 $\mu\text{S}/\text{cm}$	0 ... 1000 $\mu\text{S}/\text{cm}$
Temperature range:	-5 ... +100 °C	-5 ... +100 °C
Cell constant *:	approx. 0.1	approx. 1
Temperature measurement:	NTC 10 k	NTC 10 k
Shaft:	Stainless steel, \varnothing 12 mm x 75 mm	Glass, \varnothing 12 mm x 120 mm
Electrode:	2-pole stainless steel	2-pole glass/platinum
Application:	Pure and ultra pure water	Alcohol, fuel, diesel
cable length:	1 m	1 m



	LF 400	LF 425
Measuring range:	0 ... 200 mS/cm	0 ... 1000 mS/cm
Temperature range:	0 ... 100 °C	-10 ... +80 °C (90 °C - max.5 min)
Cell constant *:	approx. 0.55	approx. 0.42
Temperature measurement:	NTC 10 k	Pt 1000
Dimensions:	Epoxide, \varnothing 12 mm x 120 mm	PVC-C, \varnothing 16 mm x 145 mm
Characteristics:	4-pole graphite	4-pole graphite
Applications:	Universal application, Economy Class	Tight tolerances, robust and precise for highest demands, High End Class
cable length:	2 m	1 m

* Note: The particular cell constant (appears in calibration protocol and electrode's label) has to be entered to device. Then it is ready-to-use.

Accessories and spare parts:

GEH 1 Electrode holder for measuring electrodes with plastic handle (p.r.t. page 72)
GKL 100 Conductivity control solution (100 ml bottle with 1413 $\mu\text{S}/\text{cm}$ according to DIN EN 27888)
GKL 101 Conductivity control solution (250 ml bottle with 84 $\mu\text{S}/\text{cm}$)
GKL 102 Conductivity control solution (100 ml bottle with 50 $\mu\text{S}/\text{cm}$)
EBS 20M Software for long-term monitoring (p.r.t. page 77)
GSOFT 3050 Software for operation of logger devices (p.r.t. page 77)
USB 5100 Electrically isolated interface converter, supplied via USB
GNG 5 / 5000 Plug-in power supply 5 V DC, suitable for devices of the series GMH 5000 (p.r.t. page 75)
GKK 3500 Device case (394 x 294 x 106 mm) with eggcrate foam and cut-outs for 1 device (p.r.t. page 72)

Handheld instruments incl. electrode



READY-TO-USE

i. e. GMH 5450



LF 400

LF 425

GMH 5430-400

Product-ID: 602752

Handheld instrument incl. electrode LF 400

GMH 5450-400

Product-ID: 602754

Handheld instrument incl. electrode LF 400, with data logger

GMH 5430-425

Product-ID: 602753

Handheld instrument incl. electrode LF 425

GMH 5450-425

Product-ID: 602755

Handheld instrument incl. electrode LF 425, with data logger

Features:

All sets get preadjusted and are ready-for-use. They do not include a case.

Accessories and spare parts:

GKK 3500

Case with foam lining and cut-outs for 1 device (394 x 294 x 106 mm)